



XP-80

Crosslinked Polyethylene

This data sheet property values are typical of the material and are intended to provide guidance to customers; they do not constitute a specification and should not be used for specification development.

Corporate Headquarters:
1806 Conant St.
Elkhart, IN 46516

www.worldwidefoam.com

Info@worldwidefoam.com



PHYSICAL PROPERTIES	TEST METHOD	VALUES	USA UNITS	VALUES	METRIC UNITS
Density - Nominal	ASTM D3575	7.8	lb/ft ³	125	kg/m ³
Tensile Strength	ASTM D3575	TBD	psi	TBD	kPa
Tear Strength	ASTM D3575	TBD	lb/in	TBD	kg/m
Elongation	ASTM D3575	TBD	%	TBD	%
Firmness	ASTM D2240	TBD	Asker C	TBD	Asker C
Compressive Stress					
Resilience Resistance	ASTM D2632	TBD	%	TBD	%
Shrinkage Ratio (194 °F, 24h)	Internal Test	TBD	%	TBD	%
Water Absorption 7 Days		N/A	lbs./sq.ft		
Flammability		N/A	Pass/Fail	N/A	Burn Rate

For bun size and color availability, please see the color and sizing chart, or contact us at info@worldwidefoam.com or visit www.worldwidefoam.com

*Testing done according to ASTM D3575 & ASTM C177 (thermal conductivity) standards.

The data represented on this technical data sheet should be used as a guideline for product selection. This data is not intended to represent, replace or be used as a proxy for a specific product sales specification. The physical properties are averages based on limited production runs and are subject to change as additional data becomes available.